

InCide® PEST CONTROL INSULATION

LONG-LASTING PROTECTION THAT IS EFFECTIVE UNDER NORMAL USAGE AND CONDITIONS FOR INSTALLED INSULATION:

- ODORLESS AND NON-CORROSIVE
- REDUCES AIR INFILTRATION
- EXCELLENT THERMAL INSULATOR
- PATENTED FLAME RETARDANT
- SUPERIOR SOUND BARRIER
- EASY TO INSTALL

KEEP OUT OF THE REACH OF CHILDREN CAUTION

IN-CIDE® PEST CONTROL INSULATION is a ready-to-use insect control insulation. This product is toxic to listed insects and is intended to prevent their infestations in those building voids (wall, attic, under floor) where the product is applied. It works after insect contact with the product.

DIRECTIONS FOR USE:

It is a violation of Federal Law to apply this product in a manner inconsistent with its labeling.

FOR NEW CONSTRUCTION AND RETROFIT APPLICATIONS IN ATTICS, SIDEWALLS AND CRAWL SPACES: APPLY INCIDE® INTO STRUCTURAL VOIDS, COCKROACHES, ANTS, SILVERFISH, EARWIGS, CRICKETS, SOWBUGS, MILLIPEDES, CENTIPEDES AND BOOKLICE: This insulation is fused with material toxic to these insects and is intended to prevent their infestations in walls and attics where this product is applied. Control of insects is limited to contact with insulation.

DRYWOOD AND SUBTERRANEAN TERMITES: This insulation will protect wooden construction elements that are completely covered with insulation from drywood and subterranean termite infestations. This insulation is fused with material toxic to these insects and is intended to prevent new drywood and subterranean termite infestations in attics, sidewalls and crawlspace cavities where the product is applied. Protection from drywood and subterranean termites is limited to wood in direct contact with the insulation.

CAUTION

TO HELP AVOID FIRE: Keep insulation at least three inches away from the sides of recessed light fixtures. Do not place insulation over such fixtures so as to entrap heat. Also keep insulation away from exhaust flues of furnaces, water heaters, space heaters or other heat-producing devices. To be sure that insulation is kept away from light fixtures and flues, use a barrier to permanently maintain clearance around these items. Check with local building or fire officials for guidance on installation and barrier requirements.

REQUEST TO INSTALLER: Remove the label and give it to the consumer at completion of job.

COVERAGE CHART

THIS IS A NATURAL FIBER-BASE LOOSE FILL INSULATION

The manufacturer recommends the following coverage. "R" means resistance to heat flow. The higher the R-Value, the greater the insulating power. Related "R" value is per inch. Weight per bag 30 lbs. Net coverage per ASTM C-739-91 & CPSC 16-cfr PART 1209.

R-VALUE	THICKNESS (INCHES)		MAXIMUM COVERAGE				MIN. WT./SQ. FT. SETTLED
	INSTALLED	SETTLED	NET BAGS	BAGS/1000	GROSS BAGS	2X6 ON 16" CENTERS BAGS/1000	
R-11	3.3	3	67.1	14.9	73.5	13.6	0.45
R-13	3.9	3.5	56.8	17.6	63.3	15.8	0.52
R-19	5.6	5.1	39.2	25.5	43.5	23	0.76
R-24	7.2	6.5	32.3	30.9	34	29.4	0.97
R-30	9.0	8.1	24.8	40.3	27.2	36.7	1.21
R-38	11.4	10.3	19.4	51.3	21.4	46.7	1.54
R-40	12.0	10.8	18.5	54	20.4	49.1	1.62
R-45	13.5	12.1	16.4	60.8	18.1	55.2	1.82
R-50	15.1	13.5	14.8	67.6	16.3	61.3	2.02
SIDEWALLS R-13.5	2X4 FRAMED ON 16" CENTERS		40	25	WALL CAVITY SPRAY		2.50
SIDEWALLS R-21.5	2X6 FRAMED ON 16" CENTERS		28	35.7	WALL CAVITY SPRAY		2.50

To get the Marked R-Value, it is essential that this insulation be installed properly. Coverage is based upon installation using a pneumatic blowing machine. Settled density—lbs./cu.ft. Above calculations are based on settled density. Actual coverage may vary, depending on applicator technique and equipment. Installed thickness will vary depending upon conditions at the time of installation. This chart is for guidance only. Product must be installed at the coverage rates shown to obtain the listed R-Value.

STATEMENT BY MANUFACTURER

VAPOR BARRIERS: WE DO NOT RECOMMEND THE USE OF VAPOR BARRIERS WITH OUR CELLULOSE INSULATION AS DOES OUR INDUSTRY. BUT SHOULD LOCAL BUILDING CODE REQUIRE THE USE OF A VAPOR BARRIER WE RECOMMEND THAT THE WALL CAVITY (IF SPRAY APPLIED) BE ALLOWED TO CURE OR DRY.

CURE OR DRY TIME BEFORE INSTALLATION OF VAPOR BARRIERS: THERE ARE VARIABLES TO HOW LONG IT WILL TAKE THE CAVITY TO CURE OR DRY THESE ARE AMBIENT AIR TEMPERATURE, WEATHER AND DENSITY OF THE INSULATION. UNDER NO CIRCUMSTANCES IS THE INSULATION TO BE FORCE DRIED WITH HEAT. USE FANS AND OPEN DOORS AND/OR WINDOWS TO ALLOW THE MOISTURE TO ESCAPE (AMBIENT AIR ONLY). ONCE DRY THE VAPOR BARRIER MAY BE INSTALLED.

Contains No Asbestos, Glass Fibers or Formaldehyde
MADE FROM 100% NATURAL FIBER

ACTIVE INGREDIENTS:

Orthoboric Acid.....14.72%
INERT INGREDIENTS.....85.28%
TOTAL.....100.00%

EPA Reg. No. 44757-4-59737
EPA Est. No. 59737-MO-001

FOR USE IN NEW CONSTRUCTION AND RETROFIT APPLICATION IN ATTICS, SIDEWALLS AND CRAWL SPACES:

- HOUSES
- APARTMENTS
- OFFICES
- FOOD PROCESSING PLANTS
- AUTHORIZED BY USDA FOR USE IN FEDERALLY INSPECTED MEAT AND POULTRY PLANTS
- HOSPITALS
- RESTAURANTS
- SCHOOLS
- HOTELS

KILLS: Cockroaches, Ants, Drywood Termites, Subterranean Termites, Silverfish, Earwigs, Crickets, Sowbugs, Millipedes, Centipedes and Booklice

SAVINGS VARY; FIND OUT WHY IN THE SELLER'S FACT SHEET ON R-VALUES. TO GET THE MARKED R-VALUE, IT IS ESSENTIAL THAT THIS INSULATION BE INSTALLED PROPERLY. IF YOU DO IT YOURSELF, GET INSTRUCTIONS AND FOLLOW THEM CAREFULLY. INSTRUCTIONS DO NOT COME WITH THIS PACKAGE.

PRECAUTIONARY STATEMENTS: HAZARDOUS TO HUMANS AND DOMESTIC ANIMALS.

CAUTION: Harmful if swallowed. Avoid breathing dust. During installation, wear a protective respirator. To avoid eye and skin irritation, wear protective goggles and gloves. Wash thoroughly with soap and water after handling.

FIRST AID:

If Swallowed: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

If on Skin or Clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

If Inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth to mouth if possible. Call a poison control center or doctor for further treatment advice.

If in Eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. In case of emergency, for additional information, call 800-424-9300 or 800-777-4589.

PESTICIDE STORAGE AND DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Wastes resulting from this product may be disposed of on-site or at an approved waste disposal facility.

If empty: Do not reuse this container. Place in trash or offer for recycling if available.

If partly filled: Call your local solid waste agency or 1-800-CLEANUP, which is managed as a public-private partnership.

INDEPENDENT LABORATORY

TESTING: R&D Services

STANDARDS: ASTM C 739

ASTM C 1149

ASTM C 518

ASTM E 84

AMENDED CPSC STANDARD FOR RADIANT FLUX
UM-80 GUIDELINES (HUD, FHA)

IN-CIDE PC IS CLASSIFIED AS A CLASS 1
BUILDING MATERIAL



MADE WITH 100% RECYCLED PAPER,
APPROXIMATELY 77% BY WEIGHT.
PLEASE RECYCLE.

Fiberlite Technologies, Inc.

3605 E. 25th Street • Joplin, MO 64804

417-781-6380 • 800-641-4296 • Fax: 417-781-8335

www.fiberlitetech.com

MINIMUM NET WEIGHT 13.6 KGS.

BUILDERS AND APPLICATORS STATEMENT & SIGNATURE

This is to certify that the insulation has been installed in conformance with the requirements indicated on this card to provide and R-Value = _____ using _____ bags of insulation to cover _____ square feet of area.

DATE _____ BUILDER COMPANY NAME _____ BUILDER SIGNATURE _____

DATE _____ APPLICATOR COMPANY NAME _____ APPLICATOR SIGNATURE _____